



Marine & Offshore

Certificate number: 11733/E0 BV

File number: ACE 01/126/04

Product code: 2501H

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to

UNTEL KABLolari SANAYI VE TICARET A/S
KOCAELI - Türkiye

for the type of product

CABLES (LOW VOLTAGE)

0.6/1 & 1.8/3 kV

Type: MG series and M2X series.

Requirements:

BUREAU VERITAS Rules for the Classification of Steel Ships.

IEC 60092-350 (2020), IEC 60092-353 (2016), IEC 60092-360 (2021)

IEC 60228 (2004)

IEC 60332-1-2 (2015), IEC 60332-3-22 Cat.A (2018)

IEC 60331-1 (2018), IEC 60331-21 (2009)

IEC 60754-1/2 (2011)

IEC 61034-1/2 (2013)

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 31 Jul 2028

For Bureau Veritas Marine & Offshore,

At BV ISTANBUL, on 31 Jul 2023,

Gurcan Yilmaz

This certificate was created electronically and is valid without signature



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <http://www.veristarp.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=syi0gdba3k>

BV Mod. Ad.E 530 June 2017

This certificate consists of 5 page(s)

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

Flame Retardant and Fire Resistant (FFR Type only) Marine and Offshore Power, Lighting and Control cables.

1.1 - Common specifications:

Rated voltage:	0.6/1 & 1.8/3 kV
Temperature class:	90°C
Flame retardant:	IEC 60332-1 and IEC 60332-3-22 (Cat. A)
Fire resistant:	IEC 60331-1 & IEC 60331-21 (FFR Type only)
Halogen Free:	IEC 60754-1/2
Low Smoke:	IEC 61034-1/2
Fire and water spray resistant:	IEC 60331-2 + EN 50200 (WSR/WJR type)
Fire and water jet resistant:	IEC 60331-1 + BS 8491 (WSR/WJR type)

1.2 - Construction:

Conductor:	Plain or tinned stranded copper - Class 2 or class 5 (flex type)
Fire protection:	Fire Resistant Foil (FFR type)
Insulation:	XLPE (2X without WSR/WJR type) HEPR (G type) HF90 (WSR/WJR type)
Bedding and/or inner sheath and/or filler:	Bedding/Inner sheath: Halogen free & flame retardant compound Filler: Flame retardant & non hygroscopic material
Foil:	Halogen Free foil
Braiding:	Copper wires (C Type)
EMC Screen:	Electrolytic copper tape (EMC Type)
VFD Screen:	Copper / Polyester tape coverage 100% and copper wire braided screen min. coverage 90% (VFD type)
Outer Sheath:	SHF1 or SHF2

1.3 - Product Range:

Type	Number of cores	Cross sectional areas (mm ²)	Rated Voltage (kV)
MGH MGCH	1	1.5 to 400	0.6/1
	2, 3	1 to 300	
	4, 5	1 to 240	
	7 to 14	1 to 2.5	
	16 to 24	1.5 to 2.5	
	60	6	
MGH-FFR MGCH-FFR	1	2.5 to 400	
	2, 3	1 to 300	
	4, 5	1 to 240	
	7	1 to 2.5	
	10 to 37	1.5 to 2.5	
M2XH, M2XH-FFR M2XCH, M2XCH-FFR M2XCH-FFR-EMC	1	1.5 to 400	
	2, 3	1 to 300	
	4, 5	1 to 240	
	7	1 to 2.5	
	10 to 61	1.5 to 2.5	
MGCH-EMC M2XCH-EMC	3, 5	1.5 to 300	
M2XCH-FFR WSR/WJR M2XCH-FFR EMC WSR/WJR M2XH-FFR WSR/WJR	1 to 61	1 to 400	
M2XCH-VFD	1	10 to 240	
	3+3E	16+6E to 240+50E	
MGCH-SMF-EMC MGCH-FFR-EMC-SMF	3, 4	35 to 240	
MGCH-EMC MGCH-FFR-EMC	1, 3, 4	1 to 300	
	2	1 to 240	
	5	1 to 120	
	7 to 37	1.5 to 2.5	
M2XCH-VFD	1	10 to 240	0.6/1
	3+3E	16+6E to 240+50E	1.8/3

2. DOCUMENTS AND DRAWINGS:

Specification Ref. 2019_02-TS-34, rev.03, dated 09 Jan 2023.
Specification Ref. 2019_02-TS-96, rev.02, dated 09 Jan 2023.
Specification Ref. 2019_02-TS-98, rev.01, dated 10 Apr 2019.
Specification Ref. 2019-07-TS_95, rev.02, dated 08 Jan 2023.
Specification Ref. FR70-020, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-021, rev.03, dated 26 Dec 2022.
Specification Ref. FR70-030, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-031, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-041, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-044, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-050, rev.01, dated 19 Jul 2019.
Specification Ref. FR70-051, rev.01, dated 19 Jul 2019.
Specification Ref. 2019_05-TS-127, rev.05, dated 06 Oct 2019.
Specification Ref. R00_2033_01_TS_22, dated 10 Jan 2023.
Specification Ref. 2022_12-TS-10, rev.00, dated 05 Dec 2022.
Specification Ref. 2022_12-TS-12, rev.00, dated 05 Dec 2022.
Specification Ref. 2022_12-TS-8, rev.00, dated 09 Dec 2022.
Specification Ref. 2022_12-TS-20, rev.00, dated 09 Dec 2022.
Specification Ref. 2023_03_134, dated 24 Mar 2023.

3. TEST REPORTS:

VDE test report ref. 17730-9020-0001 / 32ZFM dated 2001-08-22.
 Manufacturer's test report ref. 01/09/300/1 dated 2001-09-12.
 Manufacturer's test report ref. 03/11/600 dated 2003-11-28.
 Manufacturer's test report ref. 03/11/602, dated 26.05.2005, stamped by BV.
 UNTEL KABLO A.S.: Tests on rubber and elastomer, dated 18/05/2005.
 TSE Test Report, ref. 016.01.05/05-1166, dated 14/06/2005.
 UNTEL KABLO A.S.: Routine Test Reports dated 16.03.2007.
 UNTEL KABLO A.S.: Routine Test Report Ref. 11.04 dated 09.11.2009.
 UNTEL KABLO A.S : Routine test reports dated 12/Jan./2010
 Manufacturer's test report for M2XCH cables, dated 28.12.2012, stamped by BV.
 Manufacturer's test report ref. D172480, dated 26.01.2018, stamped by BV.
 Manufacturer's test report ref. BV-2018-006-1, dated 17.01.2018, stamped by BV.
 Test reports Ref. P11733-1901-R0, P11733-1902-R0, P11733-1904-R0 and P11733-1905-R0, dated 27 Feb 2019.
 Test reports Ref. T11733-1901-R0, T11733-1902-R0 and T11733-1905-R0, dated 05 Mar 2019.
 Test reports Ref. P11733-1903-R0 and T11733-1903-R0, dated 14 Mar 2019.
 Test report Ref. T11733-1904-R0, dated 05 Apr 2019.
 Test reports Ref. MT1905-RO to MT1908-RO, dated 16 May 2019.
 Test reports Ref. MT1909-RO to MT1918-RO, dated 04 Jul 2019.
 Test report Ref. 388203, dated 07 Feb 2018.
 Test report Ref. 471761, dated 27 May 2019.
 Test reports, dated 04 Jul 2019.
 Test reports, dated 07 Jun 2022.
 Test report, dated 16 Jun 2022.
 Test report, dated 10 Jan 2023.
 Test reports Ref. T19031-R00, 19032-R00, 19033-R00, T19034-R00, T19035-R00, T19036-R00, T19037-R00 and 19038-R00, dated 03 May 2023.

4. APPLICATION / LIMITATION:

BUREAU VERITAS Rules for the Classification of Steel Ships.

5. PRODUCTION SURVEY REQUIREMENTS:

- 5.1 - The above products are to be supplied by **UNTEL KABLOLARI SANAYI VE TICARET A/S** in compliance with the type described in this certificate.
 5.2 - This type of product is within the category HBV of Bureau Veritas Rule Note NR320 and as such does not require a BV product certificate.
 5.3 - **UNTEL KABLOLARI SANAYI VE TICARET A/S** has to make the necessary arrangements to have its works recognised by Bureau Veritas in compliance with the requirements of NR320 for HBV products.
 5.4 - For information, **UNTEL KABLOLARI SANAYI VE TICARET A/S** has declared to Bureau Veritas the following production site:

UNTEL KABLOLARI SANAYI VE TICARET A/S
DEMIRCILER KOYU
MAKINE OSB
6.CADDE NO.4 41455
DILOVASI
KOCAELI
Türkiye

6. MARKING OF PRODUCT:

The cable shall be marked on the surface outer sheath, in a durable legible and visible manner, with the following information through the length of cable:

- Rated voltage
- Number of cores and cross-sectional area of the conductors
- Manufacturer's name or trademark
- Code designation (optional)

7. OTHERS:

- 7.1 - It is **UNTEL KABLOLARI SANAYI VE TICARET A/S**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.
 7.2 - This certificate supersedes the Type Approval Certificate N° 11733/D3 BV, issued on 30 Jan 2023 by the Society.

***** END OF CERTIFICATE *****